



# SAFETY DATA SHEET

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Trade name or designation of the mixture	LPS® 3 (Aerosol)
Registration number	-
Synonyms	None.
Part Number	00316, M00316
Issue date	29-August-2013
Version number	03
Revision date	06-October-2014
Supersedes date	24-September-2014

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	A specialized soft-film spray coating designed to prevent rust and corrosion on steel, aluminum and other metals.
Uses advised against	None known.

### 1.3. Details of the supplier of the safety data sheet

Supplier	Geocel Limited
Company name	Western Wood Way, Langage Science Park, Plympton,
Address	Plymouth, PL7 5BG United Kingdom
Telephone	+44 (0)1752 202060 / +44 (0)1752 334384
In Case of Emergency	+001 703-527-3887
Manufacturer	
Company name	LPS Laboratories, a division of Illinois Tool Works, Inc.
Address	4647 Hugh Howell Rd., Tucker, GA 30084 (U.S.A.)
Website	<a href="http://www.lpslabs.com">http://www.lpslabs.com</a>
e-mail	<a href="mailto:sds@lpslabs.com">sds@lpslabs.com</a>

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

#### Classification according to Directive 67/548/EEC or 1999/45/EC as amended

**Classification** F+;R12, Xn;R48/20, Xi;R36/38

The full text for all R-phrases is displayed in section 16.

#### Classification according to Regulation (EC) No 1272/2008 as amended

##### Physical hazards

Aerosols	Category 1	H222 - Extremely flammable aerosol. H229 - Pressurized container: May burst if heated.
----------	------------	---

##### Health hazards

Acute toxicity, oral	Category 4	H302 - Harmful if swallowed.
Skin corrosion/irritation	Category 2	H315 - Causes skin irritation.
Serious eye damage/eye irritation	Category 2	H319 - Causes serious eye irritation.
Specific target organ toxicity - repeated exposure (inhalation)	Category 1 (Central nervous system)	H372 - Causes damage to organs through prolonged or repeated exposure.

### Hazard summary

Physical hazards	Extremely flammable.
Health hazards	Irritating to eyes and skin. Harmful: danger of serious damage to health by prolonged exposure through inhalation. Occupational exposure to the substance or mixture may cause adverse health effects.

<b>Environmental hazards</b>	Not classified for hazards to the environment.
<b>Specific hazards</b>	Extremely flammable. Heating may cause an explosion. Do not breathe vapours, aerosols. Irritating to eyes and skin.
<b>Main symptoms</b>	Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Symptoms may include redness, oedema, drying, defatting and cracking of the skin.

## 2.2. Label elements

### Label according to Regulation (EC) No. 1272/2008 as amended

**Contains:** 1-butoxy-2-propanol, Acetone, Carbon dioxide, Distillates Petroleum Hydrotreated Heavy, Distillates Petroleum, Hydrotreated Light, Light Mineral Spirits

#### Hazard pictograms



#### Signal word

Danger

#### Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurized container: May burst if heated.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H372	Causes damage to organs through prolonged or repeated exposure.

### Precautionary statements

#### Prevention

P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe gas.
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P280	Wear protective gloves.
P280	Wear eye/face protection.

#### Response

P301 + P312	IF SWALLOWED: Call a POISON CENTRE or doctor/physician if you feel unwell.
P330	Rinse mouth.
P302 + P352	IF ON SKIN: Wash with plenty of water.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P321	Specific treatment (see this label).
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P314	Get medical advice/attention if you feel unwell.

#### Storage

P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
-------------	--

#### Disposal

P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
------	---

**Supplemental label information** 2,81 % of the mixture consists of component(s) of unknown acute oral toxicity.

**2.3. Other hazards** None known.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
Light Mineral Spirits	40 - 50	64742-88-7 265-191-7	-	649-405-00-X	

**Classification:** **DSD:** Xn;R65-48/20  
**CLP:** Asp. Tox. 1;H304, STOT RE 1;H372

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
1-butoxy-2-propanol	1 - 10	5131-66-8 225-878-4	-	603-052-00-8	
<b>Classification:</b>	<b>DSD:</b> Xi;R36/38				
	<b>CLP:</b> Acute Tox. 4;H312, Skin Irrit. 2;H315, Eye Irrit. 2;H319				
Acetone	1 - 10	67-64-1 200-662-2	-	606-001-00-8	#
<b>Classification:</b>	<b>DSD:</b> F;R11, Xi;R36, R66-67				
	<b>CLP:</b> Flam. Liq. 2;H225, Eye Irrit. 2;H319, STOT SE 3;H336				
Distillates Petroleum Hydrotreated Heavy	1 - 10	64742-54-7 265-157-1	-	649-467-00-8	
<b>Classification:</b>	<b>DSD:</b> -				L
	<b>CLP:</b> Carc. 1B;H350				L
Distillates Petroleum, Hydrotreated Light	1 - 10	64742-47-8 265-149-8	-	649-422-00-2	
<b>Classification:</b>	<b>DSD:</b> Xn;R65				
	<b>CLP:</b> Asp. Tox. 1;H304				
Carbon dioxide	1 - 5	124-38-9 204-696-9	-	-	#
<b>Classification:</b>	<b>DSD:</b> -				
	<b>CLP:</b> -				

CLP: Regulation No. 1272/2008.

DSD: Directive 67/548/EEC.

M: M-factor

vPvB: very persistent and very bioaccumulative substance.

PBT: persistent, bioaccumulative and toxic substance.

#: This substance has been assigned Community workplace exposure limit(s).

Note L: This component has been tested by Supplier. According to Supplier, the component complies with the criteria of Note L in Annex I of 67/548/EEC, and is exempt from a classification of T; R45. (Contains less than 3% DMSO)

**Composition comments** The full text for all R- and H-phrases is displayed in section 16.

## SECTION 4: First aid measures

### General information

In the case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

### 4.1. Description of first aid measures

#### Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a POISON CENTRE or doctor/physician if you feel unwell.

#### Skin contact

In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention if irritation develops and persists.

#### Eye contact

Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention if irritation develops and persists.

#### Ingestion

Call a physician or poison control centre immediately. Only induce vomiting at the instruction of medical personnel. Never give anything by mouth to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

### 4.2. Most important symptoms and effects, both acute and delayed

Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Defatting of the skin. Rash. Symptoms of overexposure can include shortness of breath, drowsiness, headaches, confusion, decreased coordination, visual disturbances and vomiting, and are reversible if exposure is stopped.

**4.3. Indication of any immediate medical attention and special treatment needed** Provide general supportive measures and treat symptomatically. In case of shortness of breath, give oxygen. Keep victim under observation. Symptoms may be delayed.

## SECTION 5: Firefighting measures

**General fire hazards** Extremely flammable aerosol.

**5.1. Extinguishing media**

**Suitable extinguishing media** Powder. Alcohol resistant foam. Carbon dioxide (CO<sub>2</sub>).

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

**5.2. Special hazards arising from the substance or mixture** Contents under pressure. Pressurised container may explode when exposed to heat or flame.

**5.3. Advice for firefighters**

**Special protective equipment for firefighters** Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

**Special fire fighting procedures** Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Water runoff can cause environmental damage.

**Specific methods** Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk. In the event of fire and/or explosion do not breathe fumes.

## SECTION 6: Accidental release measures

**6.1. Personal precautions, protective equipment and emergency procedures**

**For non-emergency personnel** Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate personal protective equipment. Do not touch or walk through spilled material. Avoid breathing gas. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.

**For emergency responders** Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.

**6.2. Environmental precautions** Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

**6.3. Methods and material for containment and cleaning up** Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. The product is immiscible with water and will spread on the water surface. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Collect spillage. Use water spray to reduce vapours or divert vapour cloud drift. Prevent product from entering drains. Following product recovery, flush area with water.

**6.4. Reference to other sections** Use personal protection recommended in Section 8 of the SDS. For waste disposal, see section 13.

## SECTION 7: Handling and storage

**7.1. Precautions for safe handling** Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not breathe gas. Do not taste or swallow. Avoid contact with skin. Avoid contact with eyes. Avoid prolonged exposure. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash hands thoroughly after handling. Avoid release to the environment. Do not empty into drains.

**7.2. Conditions for safe storage, including any incompatibilities** Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store in a well-ventilated place.

**7.3. Specific end use(s)** Not available.

## SECTION 8: Exposure controls/personal protection

**8.1. Control parameters**

**Occupational exposure limits****Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001**

<b>Components</b>	<b>Type</b>	<b>Value</b>
Acetone (CAS 67-64-1)	MAK	1200 mg/m3 500 ppm
	STEL	4800 mg/m3 2000 ppm
Carbon dioxide (CAS 124-38-9)	Ceiling	18000 mg/m3
	MAK	10000 ppm 9000 mg/m3 5000 ppm

**Belgium. Exposure Limit Values.**

<b>Components</b>	<b>Type</b>	<b>Value</b>
Acetone (CAS 67-64-1)	STEL	2420 mg/m3 1000 ppm
	TWA	1210 mg/m3 500 ppm
Carbon dioxide (CAS 124-38-9)	STEL	54784 mg/m3
	TWA	30000 ppm 9131 mg/m3 5000 ppm

**Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work**

<b>Components</b>	<b>Type</b>	<b>Value</b>
Acetone (CAS 67-64-1)	STEL	1400 mg/m3
	TWA	600 mg/m3
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm

**Croatia. Dangerous Substance Exposure Limit Values in the Workplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09**

<b>Components</b>	<b>Type</b>	<b>Value</b>
Acetone (CAS 67-64-1)	MAC	1210 mg/m3 500 ppm
	STEL	3620 mg/m3 1500 ppm
Carbon dioxide (CAS 124-38-9)	MAC	9000 mg/m3
		5000 ppm

**Cyprus. OELs. Control of factory atmosphere and dangerous substances in factories regulation, PI 311/73, as amended.**

<b>Components</b>	<b>Type</b>	<b>Value</b>
Acetone (CAS 67-64-1)	TWA	2400 mg/m3 1000 ppm
		9000 mg/m3
Carbon dioxide (CAS 124-38-9)		5000 ppm

**Czech Republic. OELs. Government Decree 361**

<b>Components</b>	<b>Type</b>	<b>Value</b>
1-butoxy-2-propanol (CAS 5131-66-8)	Ceiling	550 mg/m3
	TWA	270 mg/m3
Acetone (CAS 67-64-1)	Ceiling	1500 mg/m3
	TWA	800 mg/m3
Carbon dioxide (CAS 124-38-9)	Ceiling	45000 mg/m3
	TWA	9000 mg/m3

**Denmark. Exposure Limit Values**

<b>Components</b>	<b>Type</b>	<b>Value</b>
Acetone (CAS 67-64-1)	TLV	600 mg/m3 250 ppm

**Denmark. Exposure Limit Values**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TLV	9000 mg/m3
		5000 ppm

**Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September 2001)**

Components	Type	Value
Acetone (CAS 67-64-1)	TWA	1210 mg/m3
		500 ppm
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm

**Finland. Workplace Exposure Limits**

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	1500 mg/m3
	TWA	630 ppm
Carbon dioxide (CAS 124-38-9)	TWA	1200 mg/m3
		500 ppm
Carbon dioxide (CAS 124-38-9)	TWA	9100 mg/m3
		5000 ppm

**France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984**

Components	Type	Value
Acetone (CAS 67-64-1)	VLE	2420 mg/m3
	VME	1000 ppm
	VME	1210 mg/m3
Carbon dioxide (CAS 124-38-9)	VME	500 ppm
		9000 mg/m3
		5000 ppm

**Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)**

Components	Type	Value	Form
Acetone (CAS 67-64-1)	TWA	1200 mg/m3	
		500 ppm	
Carbon dioxide (CAS 124-38-9)	TWA	9100 mg/m3	
		5000 ppm	
Distillates Petroleum, Hydrotreated Light (CAS 64742-47-8)	TWA	140 mg/m3	Vapor and aerosol.
		20 ppm	Vapor and aerosol.

**Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace**

Components	Type	Value
Acetone (CAS 67-64-1)	AGW	1200 mg/m3
		500 ppm
Carbon dioxide (CAS 124-38-9)	AGW	9100 mg/m3
		5000 ppm

**Greece. OELs (Decree No. 90/1999, as amended)**

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	3560 mg/m3
	TWA	1780 mg/m3
Carbon dioxide (CAS 124-38-9)	STEL	54000 mg/m3
		5000 ppm
		TWA
		5000 ppm

**Hungary. OELs. Joint Decree on Chemical Safety of Workplaces**

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	2420 mg/m3
	TWA	1210 mg/m3
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3

**Iceland. OELs. Regulation 154/1999 on occupational exposure limits**

Components	Type	Value
Acetone (CAS 67-64-1)	TWA	600 mg/m3
		250 ppm
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm

**Ireland. Occupational Exposure Limits**

Components	Type	Value	
Acetone (CAS 67-64-1)	TWA	1210 mg/m3	
		500 ppm	
Carbon dioxide (CAS 124-38-9)	STEL	27000 mg/m3	
		TWA	15000 ppm
			9000 mg/m3
		5000 ppm	

**Italy. Occupational Exposure Limits**

Components	Type	Value
Acetone (CAS 67-64-1)	TWA	1210 mg/m3
		500 ppm
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm

**Latvia. OELs. Occupational exposure limit values of chemical substances in work environment**

Components	Type	Value
Acetone (CAS 67-64-1)	TWA	1210 mg/m3
		500 ppm
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm

**Lithuania. OELs. Limit Values for Chemical Substances, General Requirements**

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	2420 mg/m3
		1000 ppm
Carbon dioxide (CAS 124-38-9)	TWA	1210 mg/m3
		500 ppm
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm

**Luxembourg. Binding Occupational exposure limit values (Annex I), Memorial A**

Components	Type	Value
Acetone (CAS 67-64-1)	TWA	1210 mg/m3
		500 ppm
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm

**Malta. OELs. Occupational Exposure Limit Values (L.N. 227. of Occupational Health and Safety Authority Act (CAP. 424), Schedules I and V)**

Components	Type	Value
Acetone (CAS 67-64-1)	TWA	1210 mg/m3
		500 ppm
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm

**Netherlands. OELs (binding)**

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	2420 mg/m3
	TWA	1210 mg/m3
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3

**Norway. Administrative Norms for Contaminants in the Workplace**

Components	Type	Value
Acetone (CAS 67-64-1)	TLV	295 mg/m3
		125 ppm
Carbon dioxide (CAS 124-38-9)	TLV	9000 mg/m3
		5000 ppm

**Poland. MACs. Minister of Labour and Social Policy Regarding Maximum Allowable Concentrations and Intensities in Working Environment**

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	1800 mg/m3
	TWA	600 mg/m3
Carbon dioxide (CAS 124-38-9)	STEL	27000 mg/m3
	TWA	9000 mg/m3

**Portugal. OELs. Decree-Law n. 290/2001 (Journal of the Republic - 1 Series A, n.266)**

Components	Type	Value
Acetone (CAS 67-64-1)	TWA	1210 mg/m3
		500 ppm
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm

**Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)**

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	750 ppm
	TWA	500 ppm
Carbon dioxide (CAS 124-38-9)	STEL	30000 ppm
	TWA	5000 ppm

**Romania. OELs. Protection of workers from exposure to chemical agents at the workplace**

Components	Type	Value
1-butoxy-2-propanol (CAS 5131-66-8)	STEL	22 mg/m3
Acetone (CAS 67-64-1)	TWA	1210 mg/m3
		500 ppm
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm

**Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents**

Components	Type	Value
Acetone (CAS 67-64-1)	TWA	1210 mg/m3
		500 ppm
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm

**Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)**

Components	Type	Value
Acetone (CAS 67-64-1)	TWA	1210 mg/m3
		500 ppm
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3
		5000 ppm



**Spain. Occupational Exposure Limits**

Components	Type	Value
Acetone (CAS 67-64-1)	TWA	1210 mg/m <sup>3</sup> 500 ppm
Carbon dioxide (CAS 124-38-9)	TWA	9150 mg/m <sup>3</sup> 5000 ppm

**Sweden. Occupational Exposure Limit Values**

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	1200 mg/m <sup>3</sup> 500 ppm
	TWA	600 mg/m <sup>3</sup> 250 ppm
Carbon dioxide (CAS 124-38-9)	STEL	18000 mg/m <sup>3</sup>
	TWA	10000 ppm 9000 mg/m <sup>3</sup> 5000 ppm

**Switzerland. SUVA Grenzwerte am Arbeitsplatz**

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	2400 mg/m <sup>3</sup> 1000 ppm
	TWA	1200 mg/m <sup>3</sup> 500 ppm
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m <sup>3</sup> 5000 ppm

**UK. EH40 Workplace Exposure Limits (WELs)**

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	3620 mg/m <sup>3</sup> 1500 ppm
	TWA	1210 mg/m <sup>3</sup> 500 ppm
Carbon dioxide (CAS 124-38-9)	STEL	27400 mg/m <sup>3</sup>
	TWA	15000 ppm 9150 mg/m <sup>3</sup> 5000 ppm

**EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU**

Components	Type	Value
Acetone (CAS 67-64-1)	TWA	1210 mg/m <sup>3</sup> 500 ppm
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m <sup>3</sup> 5000 ppm

**Biological limit values****France. Biological indicators of exposure (IBE) (National Institute for Research and Security (INRS, ND 2065))**

Components	Value	Determinant	Specimen	Sampling time
Acetone (CAS 67-64-1)	100 mg/l	Acétone	Urine	*

\* - For sampling details, please see the source document.

**Germany. TRGS 903, BAT List (Biological Limit Values)**

Components	Value	Determinant	Specimen	Sampling time
Acetone (CAS 67-64-1)	80 mg/l	Aceton	Urine	*

\* - For sampling details, please see the source document.

**Slovakia. BLVs (Biological Limit Value). Regulation no. 355/2006 concerning protection of workers exposed to chemical agents, Annex 2**

Components	Value	Determinant	Specimen	Sampling time
Acetone (CAS 67-64-1)	53,36 mg/g	Acetone	Creatinine in urine	*

Slovakia. BLVs (Biological Limit Value). Regulation no. 355/2006 concerning protection of workers exposed to chemical agents, Annex 2

Components	Value	Determinant	Specimen	Sampling time
	80 mg/l	Acetone	Urine	*

\* - For sampling details, please see the source document.

Spain. Biological Limit Values (VLBs), Occupational Exposure Limits for Chemical Agents, Table 4

Components	Value	Determinant	Specimen	Sampling time
Acetone (CAS 67-64-1)	50 mg/l	Acetona	Urine	*

\* - For sampling details, please see the source document.

Switzerland. BAT-Werte (Biological Limit Values in the Workplace as per SUVA)

Components	Value	Determinant	Specimen	Sampling time
Acetone (CAS 67-64-1)	80 mg/l	Aceton	Urine	*

\* - For sampling details, please see the source document.

**Recommended monitoring procedures** Follow standard monitoring procedures.

**Derived no-effect level (DNEL)** Not available.

**Predicted no effect concentrations (PNECs)** Not available.

## 8.2. Exposure controls

**Appropriate engineering controls** Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

### Individual protection measures, such as personal protective equipment

**General information** Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. Use personal protective equipment as required.

**Eye/face protection** Wear safety glasses with side shields (or goggles). Eye wash fountain is recommended.

#### Skin protection

**- Hand protection** Chemical resistant gloves are recommended.

**- Other** Avoid contact with clothing. Wear suitable protective clothing. Chemical resistant gloves.

**Respiratory protection** No personal respiratory protective equipment normally required. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

**Thermal hazards** Not applicable.

**Hygiene measures** When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**Environmental exposure controls** Contain spills and prevent releases and observe national regulations on emissions. Environmental manager must be informed of all major releases.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Cloudy. Liquid.
<b>Physical state</b>	Gas.
<b>Form</b>	Aerosol
<b>Colour</b>	Brown.
<b>Odour</b>	Mild. Cherry.
<b>Odour threshold</b>	Not available.
<b>pH</b>	Not applicable
<b>Melting point/freezing point</b>	Not available.
<b>Initial boiling point and boiling range</b>	160 - 200 °C (320 - 392 °F)
<b>Flash point</b>	23,0 °C (73,4 °F) Tag closed cup dispensed liquid
<b>Evaporation rate</b>	0,2 (BuAc = 1)
<b>Flammability (solid, gas)</b>	Flammable gas.

## Upper/lower flammability or explosive limits

Flammability limit - lower (%) 0,6 %

Flammability limit - upper (%) 6 %

Vapour pressure 2,6 mm Hg @ 20°C

Vapour density 4,8 (Air = 1)

Relative density Not available.

## Solubility(ies)

Solubility (water) insoluble

Solubility (other) Not available.

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature 230 °C (446 °F)

Decomposition temperature Not available.

Viscosity 200 - 800 cP

Explosive properties Not available.

Oxidizing properties Not available.

## 9.2. Other information

Density 6,82 lb/gal

Percent volatile 78,45 %

Specific gravity 0,81

VOC (Weight %) 75,58 % per U.S State and Federal Consumer Product Regulations.

## SECTION 10: Stability and reactivity

**10.1. Reactivity** The product is stable and non-reactive under normal conditions of use, storage and transport.

**10.2. Chemical stability** Material is stable under normal conditions.

**10.3. Possibility of hazardous reactions** No dangerous reaction known under conditions of normal use.

**10.4. Conditions to avoid** Avoid temperatures exceeding the flash point.

**10.5. Incompatible materials** Strong oxidising agents.

**10.6. Hazardous decomposition products** Upon decomposition this product emits acrid dense smoke with carbon dioxide, carbon monoxide, water and other products of combustion.

## SECTION 11: Toxicological information

**General information** Occupational exposure to the substance or mixture may cause adverse effects.

### Information on likely routes of exposure

**Inhalation** May cause irritation to the respiratory system.

**Skin contact** Causes skin irritation.

**Eye contact** Causes serious eye irritation.

**Ingestion** May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.

**Symptoms** Irritating to eyes, respiratory system and skin. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

### 11.1. Information on toxicological effects

Components	Species	Test results
1-butoxy-2-propanol (CAS 5131-66-8)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	1400 mg/kg, 24 Hours
		1,59 ml/kg, 24 Hours
	Rat	> 2000 mg/kg, 24 Hours
<i>Inhalation</i>		
LC50	Rat	> 651 ppm, 4 Hours
<i>Oral</i>		
LD50	Rat	3300 mg/kg

Components	Species	Test results
		2,83 ml/kg
Acetone (CAS 67-64-1)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Guinea pig	> 7426 mg/kg, 24 Hours
		> 9,4 ml/kg, 24 Hours
	Rabbit	> 7426 mg/kg, 24 Hours
		> 9,4 ml/kg, 24 Hours
<i>Inhalation</i>		
LC50	Rat	55700 ppm, 3 Hours
		132 mg/l, 3 Hours
		76 mg/l, 4 Hours
		50,1 mg/l
		50,1 mg/l, 8 Hours
<i>Oral</i>		
LD50	Mouse	5,2 g/kg
	Rat	5800 mg/kg
		2,2 ml/kg
Distillates Petroleum Hydrotreated Heavy (CAS 64742-54-7)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg
		> 2000 mg/kg, 24 Hours
<i>Inhalation</i>		
LC50	Rat	2,18 mg/l, 4 Hours
<i>Oral</i>		
LD50	Rat	5000 mg/kg
Distillates Petroleum, Hydrotreated Light (CAS 64742-47-8)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg
		> 2000 mg/kg, 24 Hours
<i>Inhalation</i>		
LC50	Cat	> 6,4 mg/l, 6 Hours
	Rat	> 7,5 mg/l, 6 Hours
		> 4,3 mg/l, 4 Hours
		> 0,1 mg/l, 8 Hours
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg
Light Mineral Spirits (CAS 64742-88-7)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg
		> 2000 mg/kg, 24 Hours
<i>Inhalation</i>		
LC50	Cat	> 6,4 mg/l, 6 Hours
	Rat	> 7,5 mg/l, 6 Hours
		> 4,3 mg/l, 4 Hours
		> 0,1 mg/l, 8 Hours
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg

**Skin corrosion/irritation** Causes skin irritation.

<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation.
<b>Respiratory sensitisation</b>	Not a respiratory sensitizer.
<b>Skin sensitisation</b>	This product is not expected to cause skin sensitisation.
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
<b>Carcinogenicity</b>	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
<b>ACGIH Carcinogens</b>	
Acetone (CAS 67-64-1)	Not classifiable as a human carcinogen. A4
<b>Reproductive toxicity</b>	This product is not expected to cause reproductive or developmental effects.
<b>Specific target organ toxicity - single exposure</b>	Not classified.
<b>Specific target organ toxicity - repeated exposure</b>	May cause damage to organs (Central nervous system) through prolonged or repeated exposure.
<b>Aspiration hazard</b>	Not likely, due to the form of the product.
<b>Mixture versus substance information</b>	Not available.
<b>Other information</b>	Not available.

## SECTION 12: Ecological information

**12.1. Toxicity** Not expected to be harmful to aquatic organisms.

Components	Species	Test results
Acetone (CAS 67-64-1)		
<b>Aquatic</b>		
Crustacea	EC50 Water flea (Daphnia magna)	10294 - 17704 mg/l, 48 hours
Fish	LC50 Rainbow trout, donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours
Distillates Petroleum, Hydrotreated Light (CAS 64742-47-8)		
<b>Aquatic</b>		
Fish	LC50 Rainbow trout, donaldson trout (Oncorhynchus mykiss)	2,9 mg/l, 96 hours

**12.2. Persistence and degradability** Not inherently biodegradable.

**12.3. Bioaccumulative potential** No data available for this product.

**Partition coefficient n-octanol/water (log Kow)**  
Acetone -0,24

**Bioconcentration factor (BCF)** Not available.

**12.4. Mobility in soil** Not available.

**12.5. Results of PBT and vPvB assessment** Not available.

**12.6. Other adverse effects** None known.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

<b>Residual waste</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.
<b>EU waste code</b>	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Disposal methods/information</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

## SECTION 14: Transport information

### ADR

14.1. UN number	UN1950
14.2. UN proper shipping name	Aerosols, flammable
14.3. Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Hazard No. (ADR)	Not available.
Tunnel restriction code	Not available.
14.4. Packing group	Not applicable.
14.5. Environmental hazards	No.
14.6. Special precautions for user	Not available.

### RID

14.1. UN number	UN1950
14.2. UN proper shipping name	Aerosols, flammable
14.3. Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
14.4. Packing group	Not applicable.
14.5. Environmental hazards	No.
14.6. Special precautions for user	Not available.

### ADN

14.1. UN number	UN1950
14.2. UN proper shipping name	Aerosols, flammable
14.3. Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
14.4. Packing group	Not applicable.
14.5. Environmental hazards	No.
14.6. Special precautions for user	Not available.

### IATA

14.1. UN number	UN1950
14.2. UN proper shipping name	Aerosols, flammable
14.3. Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
14.4. Packing group	Not applicable.
14.5. Environmental hazards	No.
14.6. Special precautions for user	Not available.
Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.

### IMDG

14.1. UN number	UN1950
14.2. UN proper shipping name	Aerosols, flammable
14.3. Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
14.4. Packing group	Not applicable.

#### 14.5. Environmental hazards

Marine pollutant No

EmS Not available.

14.6. Special precautions for user Not available.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code This substance/mixture is not intended to be transported in bulk.

ADN; ADR; IATA; IMDG; RID



## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulations

**Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I**  
Not listed.

**Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex II**  
Not listed.

**Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended**  
Not listed.

**Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 1 as amended**  
Not listed.

**Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 2 as amended**  
Not listed.

**Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 3 as amended**  
Not listed.

**Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex V as amended**  
Not listed.

**Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry**  
Not listed.

**Regulation (EC) No. 1907/2006, REACH Article 59(1) Candidate List as currently published by ECHA**  
Not listed.

#### Authorisations

**Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended**  
Not listed.

#### Restrictions on use

**Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended**  
Acetone (CAS 67-64-1)

**Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work**

Distillates Petroleum Hydrotreated Heavy (CAS 64742-54-7)

**Directive 92/85/EEC: on the safety and health of pregnant workers and workers who have recently given birth or are breastfeeding**

Distillates Petroleum Hydrotreated Heavy (CAS 64742-54-7)

#### Other EU regulations

**Directive 96/82/EC (Seveso II) on the control of major-accident hazards involving dangerous substances**  
Not listed.

**Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work**  
1-butoxy-2-propanol (CAS 5131-66-8)  
Acetone (CAS 67-64-1)

Distillates Petroleum Hydrotreated Heavy (CAS 64742-54-7)  
Distillates Petroleum, Hydrotreated Light (CAS 64742-47-8)  
Light Mineral Spirits (CAS 64742-88-7)

**Directive 94/33/EC on the protection of young people at work**

Distillates Petroleum Hydrotreated Heavy (CAS 64742-54-7)  
Light Mineral Spirits (CAS 64742-88-7)

<b>Other regulations</b>	The product is classified and labelled in accordance with EC directives or respective national laws. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006.
<b>National regulations</b>	Young people under 18 years old are not allowed to work with this product according to the EU Directive 94/33/EC on the protection of young people at work.
<b>15.2. Chemical safety assessment</b>	No Chemical Safety Assessment has been carried out.

**SECTION 16: Other information**

<b>List of abbreviations</b>	Not available.
<b>References</b>	Not available.
<b>Information on evaluation method leading to the classification of mixture</b>	The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.
<b>Full text of any statements or R-phrases and H-statements under Sections 2 to 15</b>	R11 Highly flammable. R12 Extremely flammable. R36 Irritating to eyes. R36/38 Irritating to eyes and skin. R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation. R65 Harmful: may cause lung damage if swallowed. R66 Repeated exposure may cause skin dryness or cracking. R67 Vapours may cause drowsiness and dizziness. H225 Highly flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H350 May cause cancer. H372 Causes damage to organs through prolonged or repeated exposure.
<b>Revision information</b>	SECTION 2: Hazards identification: Main symptoms Composition / Information on Ingredients: Disclosure Overrides SECTION 11: Toxicological information: Acute toxicity SECTION 11: Toxicological information: Inhalation SECTION 11: Toxicological information: Specific target organ toxicity - repeated exposure SECTION 11: Toxicological information: Specific target organ toxicity - single exposure SECTION 11: Toxicological information: Symptoms Regulatory Information: Risk Phrases - Labeling HazReg Data: International Inventories GHS: Qualifiers
<b>Training information</b>	Follow training instructions when handling this material.
<b>Disclaimer</b>	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.